

Clack® 

WS1.5PCC

**WATER
SPECIALIST
CONTROL
VALVE**

NSF

Certified to NSF/ANSI/CAN 61 and NSF/ANSI/CAN 372.

- 1.5" top mount control valve suited for mid-size commercial/industrial applications
- Glass filled composite
- Economical plastic optional meter assembly
- Service flow rate of 60 gpm backwash 43 gpm
- Upflow/downflow brining field convertible
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining and current flow rate
- Four methods to initiate a regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Fully programmable regeneration cycle sequence (maximum 9)
- Programmable regeneration cycle times
- Days override feature; 1-28 days available
- Level VI 15-volt output DC power supply provides safe and easy installation
- Pre or Post treated water regenerant refill
- Low salt alarm
- Coin cell lithium battery backup for time of day up to 24 hours
- One piece expanding seal spacer stack assembly
- Patented linearly reciprocating piston operation
- Reliable and proven DC drive

Water Specialist 1.5" Plastic CC Control Specifications

Inlet/Outlet (1)	1.5" Male NPT
Cycles	up to 9
Valve Material	Glass filled composite
Regeneration	Downflow/Upflow

CONTROL VALVE FLOW RATES

Service @ 1 bar/15 psi drop (includes meter)	60 gpm
Backwash @ 1.7 bar/25 psi drop	43 gpm

OPERATING PRESSURES

Minimum/Maximum	20 - 125 psi
-----------------------	--------------

OPERATING TEMPERATURES

Minimum/Maximum	40° - 110° F
-----------------------	--------------

DIMENSIONS & WEIGHT

Distributor Pilot	
Valve bodies with 1.5" Female NPT Inlet & Outlet	1.90" OD
Drain Line Connection	1" Male Elbow NPT
Brine Line Connection	½" OD Poly Tube Compression
Mounting Base	4" - 8 UN
Height From Top Of Tank	10.75"
Shipping Weight	9 lbs.

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

	<u>U.S.</u>	<u>International</u>
Supply Voltage	100VAC to 120VAC	200VAC to 240VAC
Supply Frequency	50/60 Hz	50/60 Hz
Output Voltage	15VDC	15VDC
Output Current	500 mA	500 mA

TANK APPLICATIONS

Water Softener	12" - 24" Diameter
Water Filter (2)	12" - 24" Diameter

CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash	1 - 120 minutes
Rinse	1 - 120 minutes
Pause (service)	1 - 480 minutes
Brine (co-current)	1 - 180 minutes
Refill (softener)	0.01 - 200 lbs / .1-99 minutes
Refill (filter)	0.1 - 20.00 Gallons

Options: Backwash Filter, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot.
2. Filter tank size calculated @ 407 lpm per m² of bed area/10 gpm of backwash per square foot of bed area