

Clack®

WS1CI

WATER SPECIALIST CONTROL VALVE



Certified to NSF/ANSI 44, NSF/ANSI/CAN 61 and 372.

- Solid state microprocessor with easy access front panel settings
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Program in ppm, French degrees, German degrees, or cubic meters
- Fully programmable regeneration cycle sequence (maximum 9)
- Programmable regeneration cycle times
- Days override feature; 1 – 28 days available
- Backwash and brining ability to 21" diameter tanks
- Downflow/upflow regeneration
- Stores system configuration and operation data in nonvolatile memory
- Coin Cell Lithium battery back-up with a 24 hour carry over
- Level VI 15-volt output DC power supply provides safe and easy installation
- Control valve design provides optimum service and backwash rates
- Pre or Post treated water regenerant refill
- Mixing valve option available
- Low salt alarm
- 24-hour clock
- Reliable and proven DC drive
- One piece expanding seal spacer stack assembly
- Linearly reciprocating piston operation

Water Specialist 1" CI Control Specifications

Inlet/Outlet Fittings.....	¾" to 1.5" NPS
Cycles	up to 9
Valve Material	Fiber Reinforced Composite
Regeneration	downflow/upflow

FLOW RATES

Service @ 15 psi/1 bar drop (includes bypass and meter).....	102 lpm (6.12 m ³ /h) (27 gpm)
Backwash @ 25 psi/1.7 bar drop (includes bypass).....	102 lpm (6.12 m ³ /h) (27 gpm)

OPERATING PRESSURES

Minimum/Maximum	20 - 125 psi (1.4 - 8.6 bar)
-----------------------	------------------------------

OPERATING TEMPERATURES

Minimum/Maximum	40° - 110°F (4° - 43°C)
-----------------------	-------------------------

METER

Accuracy	± 5%
Flow Rate Range.....	0.95 - 102 lpm
Volume Range	0.02 - 5,700 m ³
Totalizer	1 m ³ - 99,999 m ³

DIMENSIONS & WEIGHT

Distributor Pilot.....	1.050" OD Pipe (¾" NPS)
Drain Line	¾" or 1" NPT
Brine Line	¾" or ½" OD Poly Tube
Mounting Base.....	2½" - 8 NPSM
Height From Top Of Tank.....	7¾" (187 mm)
Weight	4.5 lb (2 kg)

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

	<u>U.S.</u>	<u>International</u>
Supply Voltage	100VAC to 120VAC	200VAC to 240VAC
Supply Frequency	50/60 Hz.....	50/60 Hz
Output Voltage	15VDC.....	15VDC
Output Current	500 mA.....	500 mA

TANK APPLICATIONS

Water Softener	6" - 21" Diameter
Water Filter (1)	6" - 21" Diameter

CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash.....	1 - 120 minutes
Rinse.....	1 - 120 minutes
Pause (service).....	1 - 480 minutes
Brine (co-current).....	1 - 180 minutes
Brine (counter-current).....	1 - 180 minutes
Refill (softener)	0.05 - 90.00 Kg
Refill (filter)	0.2 - 76.00 Liters

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines.

1. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area.